


Temporary pedestrian walkway bridge



Quantity: 1 piece. **Material:** 0.2 mm photo-etched nickel silver coated with flat aluminum lacquer paint.

The bridge can be connected with other temporary barrier elements (Art. No. ZM-MS-008, ZM-MS-009, ZM-MS-011).

IMPORTANT: Special bending tool for metal photo etched parts required for assembly of this model!
Please read enclosed instructions inside this booklet.

ATTENTION: For fixing the bridge on layout, use non-destructive glue, such as Faller® Expert Lasercut (Art. No. 170494) or similar. Using polystyrene or cyanoacrylate glues is not recommended, as they can damage paint coating.

ZM-MS-010

Made in Ukraine


1:220

Temporary pedestrian walkway bridge

ZM-MS-010

Assembly Instructions


1. Carefully cut the bridge from the frame using precise cutter or small scissors:



 Cut


 Bend

2. Bend bridge railings upwards by 90°:



IMPORTANT: It is strongly recommended to do this step using bending tool for metal photo etched parts! Otherwise, the bridge may get damaged!

3. Carefully bend hinges into the horizontal position (by 90°) using small tweezers:



4. Bend walkway endings downwards by 15°:



NOTE: Sometimes, minor scratching of the lacquer coating may occur when using bending tool. To fix possible scratches, use Tamiya LP-38 "Flat Aluminum" lacquer paint. It can be applied manually using thin paintbrush either airbrushed. For airbrushing, it is recommended to mix Tamiya LP-38 paint with Tamiya Lacquer Thinner (Retarder Type, Art. #87194) by 50/50 proportion.